

B4



PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup> :</b> <b>H04M 1/72, 1/02</b>	<b>A1</b>	<b>(11) International Publication Number:</b> <b>WO 99/37077</b> <b>(43) International Publication Date:</b> 22 July 1999 (22.07.99)
<b>(21) International Application Number:</b> PCT/US99/01146 <b>(22) International Filing Date:</b> 20 January 1999 (20.01.99) <b>(30) Priority Data:</b> 09/009,785 20 January 1998 (20.01.98) US <b>(71) Applicant:</b> QUALCOMM INCORPORATED [US/US]; 6455 Lusk Boulevard, San Diego, CA 92121 (US). <b>(72) Inventor:</b> COOPER, Rotem; 9491 Questa Pointe, San Diego, CA 92126 (US). <b>(74) Agents:</b> OGROD, Gregory, D. et al.; Qualcomm Incorporated, 6455 Lusk Boulevard, San Diego, CA 92121 (US).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>
<b>(54) Title:</b> APPARATUS AND METHOD FOR PREVENTION OF ACCIDENTAL ACTIVATION OF KEYS IN A WIRELESS COMMUNICATION DEVICE  <b>(57) Abstract</b> <p>A wireless communication device has one or more predetermined patterns of key operation that are required to perform the function associated with the key. For example, activation of a power key on (114) a wireless communication device may be intentional or inadvertent. The wireless communication device requires activation of the selected key with a predetermined pattern of operation in order to qualify as an intentional act by the user. The predetermined patterns of operation may be varied in accordance with different conditions of the wireless communication device. The predetermined pattern of operation may require continuous activation for a predetermined period of time, multiple activation of the selected key within a predetermined period of time, simultaneous activation of multiple keys, sequential activation of multiple keys, or the like. The wireless communication device may also utilize a display to request confirmation by the user of a selected action.</p> <div data-bbox="711 1255 1458 2037"> <p>The diagram shows a perspective view of a handheld wireless communication device, labeled 100. It has a rectangular body with rounded edges. On the top surface, there is a circular power key labeled 114. To the right of the key is a small, protruding antenna labeled 112. On the front face, there is a small rectangular display or indicator labeled 108. A curved line labeled 102 indicates a hinge or a foldable part of the device. A bracket labeled 104 points to the side of the device. Another bracket labeled 106 points to the top edge of the device. The device is shown in a slightly open or angled position.</p> </div>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

# APPARATUS AND METHOD FOR PREVENTION OF ACCIDENTAL ACTIVATION OF KEYS IN A WIRELESS COMMUNICATION DEVICE

## BACKGROUND OF THE INVENTION

5

### I. Field of the Invention

The present invention is related generally to a wireless communication device and, more particularly, to an apparatus and method  
10 for preventing the accidental activation of keys in a wireless communication device.

### II. Description of the Related Art

15 Wireless communication devices, such as cellular telephones, are widely used as replacement for conventional telephone systems. Wireless communication devices offer the advantage of portability and the ability to communicate from almost any location on earth. Early wireless communication devices were large and heavy and were not widely used as  
20 replacement for conventional telephones. However, improvements in technology have resulted in the reduction in size and weight while at the same time improving the quality and reliability of wireless communications.

State of the art wireless communication devices are small  
25 enough to fit in the pocket of a user. Storing the wireless communication device in such a location may result in the inadvertent activation of keys on the wireless communication device. This is particularly problematic with the power key where inadvertent activation may turn the wireless communication device on or off without the user's knowledge. Therefore,  
30 it can be appreciated that there is a significant need for a wireless communication device and method of operation that prevents the accidental activation of keys on the wireless device. The present invention provides this and other advantages, as will be illustrated by the following description and accompanying figures.

35

## SUMMARY OF THE INVENTION

An exemplary embodiment of the present invention is directed to a system to prevent accidental activation of a key in a wireless communication device. The system comprises a housing containing the operational circuitry of the wireless communication device, a plurality of keys operable by the user to control operation of the wireless communication device, and a control circuit to sense activation of a selected one of the plurality of keys. The control circuit generates an indicator signal in response to activation of the selected key with a first pattern of operation that enables the operation of a function associated with the selected key. The control circuit is unresponsive to activation of the selected key with a second pattern of operation different from the first pattern.

Different patterns of operation may be acceptable and correspond to the first pattern of operation of the key. These include continuous activation of the selected key for a predetermined period of time, repeated activation of the selected key a predetermined number of times within a predetermined period of time, initial activation of the selected key and activation of the selected key at a subsequent time period. The subsequent time period may be a single point in time, or may comprise a time window during which the selected key must be in the active state. In one embodiment, the key must be at least momentarily in the active state within the required time window.

Other patterns of operation that correspond to the first pattern of operation can include sequential activation of the selected key and a second one of the plurality of keys within a predetermined period of time. For example, the selected key can be activated initially followed by activation of a second one of the plurality of keys within the predetermined period of time. Alternatively, the first pattern of operation may require simultaneous activation of the selected key and a second one of the plurality of keys.

In yet another alternative embodiment, the wireless communication device includes a display coupled to the housing to display text messages. In this embodiment, the first pattern of operation requires activation of the selected key and the activation of either the selected key or a second one of the plurality of keys on the key pad following the display of a confirmation request message on the display.

In another alternative embodiment, the wireless communication device includes a cover member attached to the housing and having opened and closed positions. In this embodiment, the first

pattern of operation when the cover member is in the open position is different from the first pattern of operation when the cover member is in the closed position.

## 5                    **BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1A is a perspective view of a wireless communication device designed in accordance with the principles of the present invention in a closed configuration.

10                    FIG. 1B is a front plan view of the wireless communication device of FIG. 1A in an open configuration.

FIG. 2 is a functional block diagram of the wireless communication device of FIGS. 1A and 1B.

15                    FIG. 3 is a timing diagram illustrating an acceptable predetermined pattern of key activation used by the wireless communication device of FIG. 2.

FIG. 4 is a timing diagram of an alternative acceptable predetermined pattern of key activation used by the wireless communication device of FIG. 2.

20                    FIG. 5 is a timing diagram of another alternative acceptable predetermined pattern of key activation used by the wireless communication device of FIG. 2.

25                    FIG. 6 is a timing diagram of yet another alternative acceptable predetermined pattern of key activation used by the wireless communication device of FIG. 2.

FIG. 7 is a timing diagram of yet another alternative acceptable predetermined pattern of key activation used by the wireless communication device of FIG. 2.

## 30                    **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

35                    Compact wireless communication devices often include a protective member over the keypad to prevent accidental operation of the keys. Accidental activation of the power key is prevented if the power key is also covered by the protective member. However, the disadvantage of covering the power key is that the user must open the wireless communication device to activate the power key. In an exemplary embodiment of the present invention, the power key is exposed to

advantageously provide access to the user on a continuous basis and techniques are provided to prevent accidental activation of the power key.

An exemplary embodiment of the present invention is illustrated in FIGS. 1A and 1B where a wireless communication device 100 is shown in a closed configuration in FIG. 1A. The wireless communication device 100 includes a housing 102 sized to fit easily in one hand of the user. The housing 102 includes a rotatable cover member 104. A battery housing 106 is attached to the cover member 104. A clasp 108 locks the battery housing 106 to the cover member 104 to retain the battery housing in position.

An antenna 112 projects from a top portion of the housing 102. In an exemplary embodiment, the antenna 112 is fixed. Alternatively, the antenna 112 may be extendible from the housing 102. Also included in the top portion of the housing 102 is a power key 114. The power key 114 is activated to turn the wireless communication device on and off. The advantage of locating the power key 114 on the outside portion of the housing 102 is that the wireless communication device 100 may be readily activated by the user without having to open the cover member 104 or the bottom cover member 106.

FIG. 1B illustrates the wireless communication device 100 in an open configuration with the cover member 104 in an extended operational position. An electrical switch (not shown) senses the position of the cover member 104 in the open and closed configurations. When the wireless communication device 100 is in the open configuration, a keypad 118 is exposed for operation by the user. The keypad 118 comprises individually numbered keys 120 that correspond to keys on a conventional telephone as well as control keys, such as a SEND key 122 and an END key 124. The keypad 118 may also include selection keys 126 to permit the user to select various operational features of the wireless communication device 100.

In an exemplary embodiment, the wireless communication device 100 also includes a display 130, which is exposed for viewing by the user when the wireless communication device is in the open configuration. A speaker 132 and microphone 134 are conventional components that allow two-way wireless communication.

A hinge member 138 is coupled between the cover member 104 and the housing 102 to permit the rotational movement of the cover member. In an exemplary embodiment, the hinge member 138 includes an internal spring element (not shown) to bias the cover member 104 into the

desired position in both the open configuration and the closed configuration (see FIG. 1A).

Additional components of the wireless communication device 100 are illustrated in a functional block diagram of FIG. 2. The wireless communication device 100 includes a central processing unit (CPU) 150, which controls operation of the wireless communication device. A memory 152, which may include both read-only memory and random access memory, is used to control the operation of the CPU 150. A portion of the memory 152 may also include nonvolatile random access memory. As will be described in detail below, the CPU 150 executes instructions from the memory 152 to function as a control circuit to sense operation of the power key 114 and keypad 118 and to detect operation of the keys in a manner that indicates that the user intends to activate a selected key.

A timer 154 is used by the wireless communication device 100 to measure predetermined time periods. The timer 154 may be an internal timer within the CPU 150 or an external timer under control of the CPU.

A transmitter 156 and receiver 158 allow transmission and reception of data, such as audio communications, between the wireless communication device 100 and a remote location, such as a cell-site controller (not shown). The transmitter 156 and receiver 158 may be combined into a transceiver 160. The antenna 112 is coupled to the transceiver 160.

A battery 162 is located within the battery housing 106 (see FIG. 1A) and provides power to the wireless communication device 100. In an exemplary embodiment, components such as the CPU 150, memory 152, timer 154, transmitter 156 and receiver 158 are disconnected from the battery 162 when the wireless communication device 100 is turned off. Thus, no power is consumed by the wireless communication device when it is turned off. In one embodiment, power is supplied to the CPU 150 and memory 152 upon initial activation of the power key 114 by the user. The CPU 150 executes instructions stored in the read-only memory portion of the memory 152 to initialize the CPU. The CPU 150 then executes a series of instructions designed to determine whether the user is activating the power key 114 in a manner that indicates the user's intent to turn on the wireless communication device 100. The steps taken by the CPU to determine whether the user intends to turn on the wireless communication device 100 will be discussed in detail below. If the CPU 150 determines that the user intends to turn on the wireless communication device 100, the other portions of the wireless communication device, such as the transmitter 156,

receiver 158, keypad 118, and display 130 may then be coupled to the battery 162. If the CPU 150 determines that the power key 114 was inadvertently activated, the wireless communication device 100 powers down the CPU 150 and memory 152. Alternatively, power can be applied to all portions of the wireless communication device 100 upon initial activation of the power key 114. The CPU 150 performs the steps described above to determine if the user intends to turn on the wireless communication device. If the CPU 150 determines that the user intends to turn on the wireless communication device 100, all portions of the wireless communication device are advantageously under power. However, if the CPU 150 determines that the power key 114 was inadvertently activated, the wireless communication device 100 powers down all components, including the CPU 150 and memory 152.

In yet another alternative embodiment, the battery may provide power to some portions of the wireless communication device 100 on a continuous basis. For example, the CPU may be placed in a low-power or "sleep" mode to minimize power consumption from the battery 162. The power key 114 serves as an input to the CPU 150 to place the CPU in an "awake" mode. When the user initially activates the power key 114, the CPU 150 changes from the sleep mode to the awake mode and executes the instructions to determine whether the user actually intends to turn on the wireless communication device 100. If the CPU 150 determines that the user intends to turn on the wireless communication device, the remaining portions of the wireless communication device 100 may then be coupled to the battery 162 in the manner described above. If the CPU 150 determines that the power key 114 was activated inadvertently, the CPU returns to the sleep mode.

The various components of the wireless communication device 100 are coupled together by a bus system 166, which may include a power bus, control signal bus, and status signal bus in addition to a data bus. However, for the sake of clarity, the various buses are illustrated in FIG. 2 as the bus system 166.

A conventional wireless communication device allows activation of power key simply by depressing the power key. However, such operation can lead to accidental activation of the power key. The present invention is designed to sense user activation of the power key 114 and will only respond to user activation of the power key under a predetermined set of conditions.



In an exemplary embodiment, the user must activate the power key 114 for a predetermined period of time before the wireless communication device 100 responds to activation of the power key. This is illustrated in FIG. 3 where the wireless communication device 100 detects  
5 initial activation of the power key 114 at a time designated as  $t_0$ . The wireless communication device 100 continues to monitor the state of the power key 114 until a predetermined time designated in FIG. 3 as  $t_1$ . If the power key 114 is continuously activated for the entire time period between time  $t_0$  and time  $t_1$ , the wireless communication device 100 responds to the  
10 activation of the power key. In an exemplary embodiment, the wireless communication device 100 may require continuous activation of the power key 114 for a period of three seconds. The continuous activation of the power key 114 for time period from time  $t_0$  to time  $t_1$  illustrates a first pattern of operation of the key that is unlikely to result from inadvertent jostling of  
15 the wireless communication device 100 and serves as an indicator that the user actually intends to activate power key 114. A second pattern of operation, such as momentary activation of the power key 114 for a time less than the time period from time  $t_0$  to time  $t_1$ , is unlikely to be the result of intentional activation by the user and will thus be ignored by the wireless  
20 communication device 100.

In the example of the first pattern of operation, illustrated in FIG. 3, the wireless communication device 100 continuously monitors the state of the power key 114 during the time period from time  $t_0$  to time  $t_1$ . In an alternative embodiment, illustrated in FIG. 4, the wireless  
25 communication device 100 detects initial activation of the power key 114 at time  $t_0$  and simply samples the state of the power key again at time  $t_1$  rather than continuously monitor the state of the power key. The power key 114 has a first logic state when in an inactivated position and a second logic state when activated. If the power key 114 is activated (*i.e.*, in the second logic state) at the time  $t_1$ , the wireless communication device 100 will respond to  
30 user activation of the power key.

In another alternative embodiment, illustrated in FIG. 5, the wireless communication device 100 detects initial activation of the power key 114 at time  $t_0$ . Instead of continuously monitoring the state of the power  
35 key 114, the wireless communication device 100 samples the state of the power key during a time window that follows the detection of the initial activation of the power key at time  $t_0$ . The time window is designated in FIG. 5 by the references  $t_2$  and  $t_3$ . The start of the time window occurs at a predetermined time  $t_2$  after initial activation of the power key 100 at time  $t_0$

and ends at a predetermined time  $t_3$  after initial activation of the power key. If the power key 114 is activated at the initial time  $t_0$  and is in the active state at any time during the time window between time  $t_2$  and time  $t_3$ , the wireless communication device 100 responds to activation of the power key.

- 5 In an exemplary embodiment, the time window is approximately 200 milliseconds with the start of the time window, indicated by time  $t_2$ , occurring approximately three seconds after the initial activation of the power switch 114 at time  $t_0$ .

- Numerous alternative techniques may be used to detect the user's intent to actually activate the power key 114. For example, the wireless communication device 100 can monitor the state of the power key 114 and detect multiple activations of the power key within a predetermined time period. This is illustrated in FIG. 6 where the initial activation of the power key 114 is detected at time  $t_0$ . In accordance with this embodiment of the invention, the user must activate the power key 114 a plurality of times between the initial activation at time  $t_0$  and a predetermined time designated in FIG. 6 as time  $t_4$ . In the example illustrated in FIG. 6, the user must activate the power key 114 three times within the predetermined time period between time  $t_0$  and time  $t_4$ , which may be, by way of example, a three-second time period.

- The various techniques described above and illustrated in FIG. 3 to FIG. 6 illustrate techniques used to determine when the user actually wants to activate the power key 114. The wireless communication device performs this task by detecting user operation of the power key in one of the predetermined patterns described above. Alternatively, other patterns of user operation of the power key 114 may be used satisfactorily with the wireless communication device 100. In addition, combinations of the different patterns of user operation may be used satisfactorily with the wireless communication device 100. For example, the CPU 150 may be programmed to recognize multiple different patterns of activity as acceptable. Continuous activation of the power key 114 for the predetermined period of time (e.g., three seconds) or activating the power key multiple times within the predetermined period of time may both be recognized by the CPU 150 as corresponding to an acceptable pattern of user operation of the power key. Accordingly, user operation of the power key in any combination of acceptable patterns of activity may be used by the wireless communication device 100.

In the exemplary embodiment of the wireless communication device 100 illustrated in FIGS. 1A and 1B, the power key 114 is located on the

top portion of the housing 102 and is thus continuously exposed for easy activation by the user. The various patterns of operation described above and illustrated in FIG. 3 to FIG. 6 may be used when the wireless communication device 100 is in the closed configuration, illustrated in FIG.

5 1A. However, an altered first pattern of operation may be used when the wireless communication device 100 is in the open configuration, illustrated in FIG. 1B. The electrical switch (not shown) coupled to the hinge member 138 is used to sense whether the wireless communication device 100 is in the open configuration or closed configuration.

10 The altered patterns of operation of the power key 114 reflect the fact that the user is actively using the wireless communication device 100 in the open configuration and likely intends to activate the power key 114. For example, momentary activation of the power key 114 at time  $t_0$ , as illustrated in FIG. 7, may be used as the first pattern of operation when the  
15 wireless communication device 100 is in the open configuration. Alternatively, the activation pattern illustrated in FIG. 3, requiring continuous activation from the time of initial activation at time  $t_0$  to time  $t_1$ , may be used, but with the time period being altered to reflect the fact that the wireless communication device is in the open configuration. For example,  
20 the time period from time  $t_0$  to time  $t_1$  may be three seconds when the wireless communication device 100 is in the closed configuration (see FIG. 1A), while the time period from time  $t_0$  to  $t_1$  may be only one second when the wireless communication device is in the open configuration (see FIG. 1B). Similarly, the wireless communication device 100 can sample the state  
25 of the power key 114 at a predetermined time  $t_1$  after initial activation at time  $t_0$  or using the time window from time  $t_2$  to time  $t_3$  as illustrated in FIG. 4 and FIG. 5, but with altered time periods to reflect that the wireless communication device is in the open configuration.

The wireless communication device 100 may also use the first  
30 pattern of operation for the power key 114 to turn on the wireless communication device 100 and an altered first pattern of operation to turn off the wireless communication device. For example, if the wireless communication device 100 is in the open configuration (see FIG. 1B) only a momentary activation of the power key 114 may be required to turn on the  
35 wireless communication device 100, as illustrated in FIG. 7. However, continuous activation of the power key 114 for a period of time, as illustrated in FIG. 3, may be required to turn off the wireless communication device 100.

The wireless communication device 100 illustrated in FIG. 1A exposes only the power key 114 in the closed configuration. However, alternative embodiments of the wireless communication device 100 may be employed in which other keys, such as the selection keys 126 (see FIG. 1B), may also be exposed. The predetermined first pattern of operation may require activation of more than one key, such as the power key 114 and one of the selection keys 126. Various patterns of operation that correspond to the accepted first pattern of operation may include simultaneous activation of the power key 114 and one of the selection keys 126 or the sequential activation of the power key 114 and the selection key 126 within a predetermined period of time.

The wireless communication device 100 may also generate a prompt requiring additional activation of one or more keys on the keypad 118 (see FIG. 1B and FIG. 2) to perform the desired function. For example, the wireless communication device 100 may use a prompt on the display 130 in response to an initial momentary activation of the power key 114, as illustrated in FIG. 7. The display 130 can be programmed to display a prompt requesting that the user activate the power key 114 or a specified one of the selection keys 126 to confirm that the wireless communication device 100 is being turned off. The first pattern of operation may require that the activation of the power key 114 or selection key 126 in response to the prompt occur within a predetermined time of the display of the prompt.

Other acceptable first patterns of operation are dependent on the position of the cover member 104. For example, assuming the wireless communication device 100 is turned on and is in the open configuration (see FIG. 1B), momentary activation of the power key 114 followed by closure of the cover member 104 within a predetermined period of time serves as an indication that the user intends to turn off the wireless communication device. Similarly, assuming that the wireless communication device 100 is turned off and is in the closed configuration (see FIG. 1A), momentary activation of the power key 114 followed by an opening of the cover member 104 within a predetermined period of time serves as an indication that the user intends to turn on the wireless communication device.

Thus, a number of different patterns of operation of the various keys on the wireless communication device 100 serve as satisfactory indicators of the user's intent to perform a particular function. While the examples above are directed to the use of the power key 114, it is clear that the principles of the present invention may be applied to the activation of other keys as well. For example, additions or deletions to prestored speed

dialing numbers within the memory 104 (see FIG. 2) may require the activation of keys with a predetermined pattern of operation, such as the simultaneous activation of keys, activation of keys in a sequential manner, or the like. Similarly, the principles of the present invention may be applied  
5 to a wireless communication device that has all keys continuously exposed where the keys may be inadvertently activated.

It is to be understood that even though various embodiments and advantages of the present invention have been set forth in the foregoing description, the above disclosure is illustrative only, and changes  
10 may be made in detail, yet remain within the broad principles of the invention. For example, a combination of different patterns of operation may serve as satisfactory indicators the user's intent to perform a particular function. In addition, different patterns of operation may be valid only at certain operational states of the wireless communication device 100. For  
15 example, certain patterns of operation, or combinations of patterns of operation, may be used when the wireless communication device is initially turned on. Following completion of a call, one or more different patterns of operation may be used to turn the wireless communication device off. Thus, multiple patterns of operation, combinations of patterns of operation,  
20 and state-dependent patterns of operation may be used by the wireless communication device 100. Accordingly, the present invention is to be limited only by the appended claims.

WE CLAIM

## CLAIMS

1. A wireless communication device comprising:  
2 a housing, sized to be held in a hand of a user;  
a wireless communication circuit within the housing to  
4 transmit wireless communications to a location remote from the wireless  
communication device and to receive wireless communications from a  
6 location remote from the wireless communication device;  
an antenna coupled to the housing to transmit radio signals  
8 generated by the wireless communication circuit and to detect wireless  
transmissions from the location remote from the wireless communication  
10 device;  
a keypad coupled to the housing and having a plurality of keys  
12 operable by the user to control operation of the wireless communication  
device;  
14 a cover member, attached to the housing and having open and  
closed positions, the cover member concealing the keypad when in the  
16 closed position to prevent accidental activation thereof, the cover member  
exposing the keypad when in the open position to permit activation thereof;  
18 a power supply within the housing and selectively activated to  
provide power to the wireless communication device;  
20 a power control mounted on the housing and continuously  
exposed to permit activation by a user to turn on and turn off the wireless  
22 communication device; and  
a power control circuit to sense activation of the power control  
24 and to generate an indicator signal in response to activation of the power  
control with a first pattern of operation, the power control circuit being  
26 unresponsive to a activation of the power control with a second pattern of  
operation different from the first pattern, the indicator signal enabling  
28 operation of the power supply.

2. The wireless communication device of claim 1 wherein  
2 the first pattern of operation when the cover member is in the open position  
is different from the first pattern of operation when the cover member is in  
4 the closed position.

3. The wireless communication device of claim 1 wherein  
2 the first pattern of operation requires continuous activation of the power  
control for a predetermined period of time.

4. The wireless communication device of claim 3 wherein  
2 the predetermined period of time when the cover member is in the open  
position is different from the predetermined period of time when the cover  
4 member is in the closed position.

5. The wireless communication device of claim 1 wherein  
2 the first pattern of operation requires activation of the power control a  
predetermined number of times within a predetermined period of time.

6. The wireless communication device of claim 1 wherein  
2 the power control has a first state when activated and a second state when  
not activated and the first pattern of operation requires initial activation of  
4 the power control and requires that the power control is in the first state at a  
predetermined time following the initial activation.

7. The wireless communication device of claim 1 wherein  
2 the power control has a first state when activated and a second state when  
not activated and the first pattern of operation requires initial activation of  
4 the power control and requires that the power control is in the first state  
between a first predetermined time following the initial activation and a  
6 second predetermined time following the first predetermined time.

8. The wireless communication device of claim 7 wherein  
2 the first pattern of operation requires that the power control is at least  
momentarily in the first state between the first predetermined time  
4 following the initial activation and the second predetermined time  
following the first predetermined time.

9. The wireless communication device of claim 1 wherein  
2 the first pattern of operation requires sequential activation of the power  
control and a selected one of the plurality of keys on the keypad within a  
4 predetermined period of time.

10. The wireless communication device of claim 9 wherein  
2 the first pattern of operation requires sequential activation of the power

control followed by activation of the selected one of the plurality of keys on  
4 the keypad within the predetermined period of time.

11. The wireless communication device of claim 1 wherein  
2 the first pattern of operation requires simultaneous activation of the power  
control and a selected one of the plurality of keys on the keypad.

12. The wireless communication device of claim 1, further  
2 including a display coupled to the housing to display text messages and  
wherein the first pattern of operation requires activation of the power  
4 control and a activation of a selected one of the plurality of keys on the  
keypad following the display of a confirmation request message on the  
6 display.

13. The wireless communication device of claim 1 wherein  
2 the power control circuit is responsive to activation of the power control  
with a plurality of first patterns of operation, the power control circuit  
4 generating the indicator signal in response to activation of the power control  
with any of the plurality of first patterns of operation.

14. The wireless communication device of claim 1 having a  
2 plurality of operational states wherein the power control circuit is  
responsive to activation of the power control with a first pattern of  
4 operation corresponding to each of the plurality of operational states, the  
power control circuit generating the indicator signal in response to  
6 activation of the power control with the first pattern of operation  
corresponding to the operational state of the wireless communication  
8 device.

15. A system to prevent accidental activation of a key in a  
2 wireless communication device, the system comprising:  
a housing containing the operational circuitry of the wireless  
4 communication device;  
a plurality of keys operable by the user to control operation of  
6 the wireless communication device; and  
a control circuit to sense activation of a selected one of the  
8 plurality of keys and to generate an indicator signal in response to activation  
of the selected key with a first pattern of operation, the control circuit being  
10 unresponsive to activation of the selected key with a second pattern of



operation different from the first pattern, the indicator signal enabling  
12 operation of a function associated with the selected key.

16. The system of claim 15, further including a cover  
2 member, attached to the housing and having open and closed positions,  
wherein the first pattern of operation when the cover member is in the  
4 open position is different from the first pattern of operation when the cover  
member is in the closed position.

17. The system of claim 15 wherein the first pattern of  
2 operation requires continuous activation of the selected key for a  
predetermined period of time.

18. The system of claim 15 wherein the first pattern of  
2 operation requires activation of the selected key a predetermined number of  
times within a predetermined period of time.

19. The system of claim 15 wherein the selected key has a  
2 first state when activated and a second state when not activated and the first  
pattern of operation requires initial activation of the selected key and  
4 requires that the selected key is in the first state at a predetermined time  
following the initial activation.

20. The system of claim 15 wherein the selected key has a  
2 first state when activated and a second state when not activated and the first  
pattern of operation requires initial activation of the selected key and  
4 requires that the selected key is in the first state between a first  
predetermined time following the initial activation and a second  
6 predetermined time following the first predetermined time.

21. The system of claim 20 wherein the first pattern of  
2 operation requires that the selected key is at least momentarily in the first  
state between the first predetermined time following the initial activation  
4 and the second predetermined time following the first predetermined time.

22. The system of claim 15 wherein the first pattern of  
2 operation requires sequential activation of the selected key and a second one  
of the plurality of keys within a predetermined period of time.

23. The system of claim 22 wherein the first pattern of  
2 operation requires sequential activation of the selected key followed by  
activation of the second one of the plurality of keys within the  
4 predetermined period of time.

24. The system of claim 15 wherein the first pattern of  
2 operation requires simultaneous activation of the selected key and a second  
one of the plurality of keys.

25. The system of claim 15, further including a display  
2 coupled to the housing to display text messages and wherein the first pattern  
of operation requires activation of the selected key and a activation of a  
4 second one of the plurality of keys on the keypad following the display of a  
confirmation request message on the display.

26. The wireless communication device of claim 15 wherein  
2 the control circuit is responsive to activation of the selected key with a  
plurality of first patterns of operation, the control circuit generating the  
4 indicator signal in response to activation of the selected key with any of the  
plurality of first patterns of operation.

27. The wireless communication device of claim 15 having a  
2 plurality of operational states wherein the control circuit is responsive to  
activation of the selected key with a first pattern of operation corresponding  
4 to each of the plurality of operational states, the control circuit generating  
the indicator signal in response to activation of the selected key with the first  
6 pattern of operation corresponding to the operational state of the wireless  
communication device.

28. A method to prevent accidental activation of a selected  
2 one of a plurality of keys on a wireless communication device, the method  
comprising the steps of:  
4       sensing activation of a selected one of the plurality of keys;  
      generating an indicator signal in response to the activation of  
6 the selected key with a first pattern of operation, and being unresponsive to  
the activation of the selected key with a second pattern of user operation  
8 different from the first pattern; and  
      enabling operation of a function associated with the selected  
10 key if the indicator signal is generated.

29. The method of claim 28 for use with a wireless communication device including a cover member having open and closed positions, wherein the first pattern of operation when the cover member is in the open position is different from the first pattern of operation when the cover member is in the closed position.

30. The method of claim 28 wherein the first pattern of operation requires continuous activation of the selected key for a predetermined period of time.

31. The method of claim 28 wherein the first pattern of operation requires activation of the selected key a predetermined number of times within a predetermined period of time.

32. The method of claim 28 wherein the selected key has a first state when activated and a second state when not activated and the first pattern of operation requires initial activation of the selected key and requires that the selected key is in the first state at a predetermined time following the initial activation.

33. The method of claim 28 wherein the selected key has a first state when activated and a second state when not activated and the first pattern of operation requires initial activation of the selected key and requires that the selected key is in the first state between a first predetermined time following the initial activation and a second predetermined time following the first predetermined time.

34. The method of claim 33 wherein the first pattern of operation requires that the selected key is at least momentarily in the first state between the first predetermined time following the initial activation and the second predetermined time following the first predetermined time.

35. The method of claim 28 wherein the first pattern of operation requires sequential activation of the selected key and a second one of the plurality of keys within a predetermined period of time.

36. The method of claim 35 wherein the first pattern of operation requires sequential activation of the selected key followed by

activation of the second one of the plurality of keys within the  
4 predetermined period of time.

37. The method of claim 28 wherein the first pattern of  
2 operation requires simultaneous activation of the selected key and a second  
one of the plurality of keys.

38. The method of claim 28 for use with a wireless  
2 communication device having a display to display text messages and  
wherein the first pattern of operation requires activation of the selected key  
4 and a activation of a second one of the plurality of keys on the keypad  
following the display of a confirmation request message on the display.

39. The method of claim 28 wherein the step of generating  
2 the indicator signal is responsive to activation of the selected key with a  
plurality of first patterns of operation and generates the indicator signal in  
4 response to activation of the selected key with any of the plurality of first  
patterns of operation.

40. The method of claim 28 for use with a wireless  
2 communication device having a plurality of operational states wherein the  
step of generating the indicator signal is responsive to activation of the  
4 selected key with a first pattern of operation corresponding to each of the  
plurality of operational states and generates the indicator signal in response  
6 to activation of the selected key with the first pattern of operation  
corresponding to the operational state of the wireless communication  
8 device.

1/5




FIG. 1A




FIG. 1B

3/5




FIG. 2

100

4/5




FIG. 3




FIG. 4




FIG. 5



5/5




FIG. 6




FIG. 7

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 99/01146

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 H04M1/72 H04M1/02

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	EP 0 776 116 A (NOKIA MOBILE PHONES LTD) 28 May 1997  see column 1, line 1-17 see column 1, line 36 - column 2, line 33 see column 4, line 19-31 see column 5, line 42-56	15, 17, 22, 28, 30, 35, 36
A	---	1, 3, 9, 10, 12, 24, 25, 37, 38
X	US 5 247 565 A (JOGLEKAR MANOHAR A ET AL) 21 September 1993 see abstract; claims 1, 2	15, 24, 28, 37
A	---	11
	-/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

16 April 1999

Date of mailing of the international search report

29/04/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

de Biolley, L

# INTERNATIONAL SEARCH REPORT

Inter.      nal Application No  
PCT/US 99/01146

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 97 31468 A (NOKIA MOBILE PHONES LTD ;CRISP MARTIN (GB)) 28 August 1997 see page 7, line 3 - page 8, line 4	1,2
A	EP 0 346 639 A (MOTOROLA INC) 20 December 1989 see claims 1,2	1,2

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/01146

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0776116 A	28-05-1997	US 5812954 A	22-09-1998
US 5247565 A	21-09-1993	US 5117450 A	26-05-1992
		BR 9205507 A	05-04-1994
		CA 2097808 A,C	22-04-1993
		GB 2266211 A,B	20-10-1993
		KR 9616367 B	09-12-1996
		MX 9205994 A	01-05-1993
		WO 9308615 A	29-04-1993
		AU 621752 B	19-03-1992
		AU 5569590 A	18-12-1990
		CA 2032163 A,C	11-11-1990
		CN 1047181 A	21-11-1990
		EP 0431096 A	12-06-1991
		JP 3506109 T	26-12-1991
		KR 9409476 B	13-10-1994
		MX 173350 B	22-02-1994
		WO 9014729 A	29-11-1992
WO 9731468 A	28-08-1997	GB 2310561 A	27-08-1997
		AU 1887397 A	10-09-1997
		AU 1889897 A	10-09-1997
		EP 0883956 A	16-12-1998
		EP 0883957 A	16-12-1998
		GB 2310562 A	27-08-1997
		WO 9731469 A	28-08-1997
EP 0346639 A	20-12-1989	US 4845772 A	04-07-1989
		AT 142068 T	15-09-1996
		AU 610416 B	16-05-1991
		AU 3741189 A	12-01-1990
		CA 1296774 A	03-03-1992
		DE 68927024 D	02-10-1996
		DE 68927024 T	06-03-1997
		DK 30190 A	27-03-1990
		ES 2091189 T	01-11-1996
		IE 61916 B	30-11-1994
		IN 169068 A	31-08-1991
		JP 2007117 C	11-01-1996
		JP 2044843 A	14-02-1990
		MX 165350 B	05-11-1992
		WO 8912945 A	28-12-1989